

according to Regulation (EC) No 1907/2006

HANSA-FLEX OEL HVLPD 46

Revision date: 03.07.2024

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

HANSA-FLEX OEL HVLPD 46

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Hydraulic oil. Product Categories [PC]: PC 17 Hydraulic fluids.

1.3. Details of the supplier of the safety data sheet

no. Botano or the supplier of the		
Company name:	HANSA-FLEX AG	
Street:	Zum Panrepel 44	
Place:	D-28307 Bremen	
Telephone:	+49 (0) 421 48907 0	Telefax: +49 (0) 421 48907 48
E-mail:	info@hansa-flex.com	
Contact person:	Service	
E-mail:	info@hansa-flex.com	
Internet:	www.hansa-flex.de	
1.4. Emergency telephone	+49 (0) 551 19240	
number:	Giftinformationszentrum - Nord	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is not classified as hazardous in accordance with Regulation (EC) No 1272/2008.

2.2. Label elements

Additional advice on labelling

Identification is not obligatory.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. Do not handle until all safety precautions have been read and understood. Discharge into the environment must be avoided.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Contains: Mineral oil, Additive.

Further Information

The mineral oils in the product contain < 3 % DMSO-extract (IP 346).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Move victim out of danger zone. Remove contaminated, saturated clothing immediately. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data



according to Regulation (EC) No 1907/2006

HANSA-FLEX OEL HVLPD 46

Revision date: 03.07.2024

sheet if possible).

After inhalation

Avoid oil mist

Move victim to fresh air. Put victim at rest and keep warm. Get medical advice/attention if you feel unwell.

After contact with skin

After contact with skin, wash immediately with: Water and soap. Immediately remove any contaminated clothing, shoes or stockings. In case of skin irritation, seek medical treatment.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Call a physician immediately. No administration in cases of unconsiousness or cramps.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam, Extinguishing powder, Water mist, Carbon dioxide (CO2).

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon dioxide (CO2), Sulphur dioxide (SO2), Phosphorus oxides, Carbon monoxide.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. In case of fire: Wear self-contained breathing apparatus.

Additional information

Move undamaged containers from immediate hazard area if it can be done safely. Use water spray jet to protect personnel and to cool endangered containers. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation.

- Respiratory protection necessary at: aerosol or mist generation. (See section 8.)
- Avoid contact with skin and eyes. Wear personal protection equipment.
- In case of leakage, eliminate all ignition sources. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Page 2 of 8

HANSA

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HANSA-FLEX OEL HVLPD 46

Revision date: 03.07.2024

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

Other information

Prevent spread over a wide area (e.g. by containment or oil barriers). Take up mechanically, placing in appropriate containers for disposal. Remove from the water surface (e.g. skimming, sucking). High slip hazard because of leaking or spilled product. Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Personal protection equipment: refer to chapter 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Do not breathe vapour/aerosol. Provide adequate ventilation. Avoid contact with skin and eyes. Remove contaminated, saturated clothing immediately.

For industrial purposes only.

Advice on protection against fire and explosion

No special fire protection measures are necessary. Avoid oil mist When hot, product develops flammable vapours. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Fire class B (DIN EN 2).

Advice on general occupational hygiene

Do not eat, drink, smoke or sneeze at the workplace.

Avoid contact with skin, eyes and clothes.

Protect skin by using skin protective cream.

Take off contaminated clothing and wash it before reuse.

Wash hands before breaks and after work.

After cleaning apply high-fat content skin care cream.

Do not put any product-impregnated cleaning rags into your trouser pockets.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Only use containers specifically approved for the substance/product. Keep container tightly closed and in a well-ventilated place. Always close containers tightly after the removal of product. Recommended storage temperature: 5 - 30 °C. Do not store at temperatures over: 40 °C

Hints on joint storage

Do not store together with: Oxidising agent, Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions

Protect against: Heat, Light, moisture. Protect from direct sunlight.

7.3. Specific end use(s)

Hydraulic oil. Observe technical data sheet.





according to Regulation (EC) No 1907/2006

HANSA-FLEX OEL HVLPD 46

Revision date: 03.07.2024

Page 4 of 8

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional advice on limit values

Air limit values: Mineral oil mist Limit value type (country of origin): US-OSHA PEL-Value: 5 mg/m³ Limit value type (country of origin): ACGIH STEL-Value: 10 mg/m³

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: Tightly sealed safety glasses. (EN 166)

In case of increasing hazard add: Eye-shade.

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN 420, EN ISO 374.

Suitable material: NBR (Nitrile rubber), PVC (polyvinyl chloride), FKM (fluororubber).

Required properties: liquid-tight.

penetration time (maximum wearing period): > 240 min.

Thickness of glove material: 0,4 mm

Before using check leak tightness / impermeability.

Skin protection

Handling larger quantities: Wear suitable protective clothing.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required. Respiratory protection necessary at: exceeding exposure limit values, insufficient ventilation, aerosol or mist generation.

Suitable respiratory protective equipment: A2, A2/P2 Combination filter device (DIN EN 141)...

Environmental exposure controls

Make sure spills can be contained, e.g. in sump pallets or kerbed areas.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Colour: Odour:	liquid light yellow - yellow like: mineral oil.	
Odour.		Test method
Changes in the physical state		
Melting point/freezing point:	No data available.	
Boiling point or initial boiling point and boiling range:	> 320 °C	
Pour point:	< -30 °C	DIN ISO 3016
Flash point:	> 220 °C	DIN ISO 2592
Flammability Solid/liquid:	Based on available data, the classification criteria are	

not met.





according to Regulation (EC) No 1907/2006

HANSA-FLEX OEL HVLPD 46

Revision date: 03.07.2024 Page 5 of 8 **Explosive properties** Based on available data, the classification criteria are not met. Lower explosion limits: approx. 0,6 vol. % Upper explosion limits: approx. 6,5 vol. % Auto-ignition temperature: > 220 °C DIN 51794 No data available. Decomposition temperature: **Oxidizing properties** Based on available data, the classification criteria are not met. pH-Value: not applicable Viscosity / kinematic: approx. 46 mm²/s DIN 51562 (at 40 °C) practically insoluble Water solubility: Vapour pressure: < 0,1 hPa (at 20 °C) Density (at 15 °C): approx. 0,85 - 0,87 g/cm3 DIN 51757 9.2. Other information Information with regard to physical hazard classes No data available Sustaining combustion: Other safety characteristics 0% Solvent content: **Further Information** none

SECTION 10: Stability and reactivity

10.1. Reactivity

No risks worthy of mention.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures. Decompositon takes place from temperatures above: 150 °C

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions. Do not mix with: Oxidizing agents, strong.

10.4. Conditions to avoid

storage stability: Do not store at temperatures over: 40 °C This material is combustible, but will not ignite readily. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

10.5. Incompatible materials

Oxidizing agents, strong.

10.6. Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapours. In case of fire may be liberated: Carbon dioxide (CO2), Sulphur dioxide (SO2), Phosphorus oxides, Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008



according to Regulation (EC) No 1907/2006

HANSA-FLEX OEL HVLPD 46

Revision date: 03.07.2024

Page 6 of 8

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Irritation and corrosivity

Irritant effect on the skin: On short hand contact: non-irritant.

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

Irritant effect on the eye: slightly irritant but not relevant for classification.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met. The mineral oils in the product contain < 3 % DMSO-extract (IP 346).

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

No information available.

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria).

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

State of matter: liquid at room temperature.

If product enters soil, it will be mobile and may contaminate groundwater

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Discharge into the environment must be avoided. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations



according to Regulation (EC) No 1907/2006

HANSA-FLEX OEL HVLPD 46

Revision date: 03.07.2024

Page 7 of 8

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to "Kreislaufwirtschafts- und Abfallgesetz (KrW-/AbfG)". Dispose of waste according to applicable legislation.

The waste key according to the European Waste Catalogue (EWC number) refers to the real wastes origin and therefore is not product- but use-oriented.

Consult the local waste disposal expert about waste disposal.

Observe mixture permissions according to "Altölverordnung (Waste oil directive)".

List of Wastes Code - residues/unused products

130110 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste hydraulic oils; mineral based non-chlorinated hydraulic oils; hazardous waste

List of Wastes Code - used product

130110 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste hydraulic oils; mineral based non-chlorinated hydraulic oils; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be disposed of.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: 14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

Inland waterways transport (ADN)

14.1. UN number or ID number:

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

Marine transport (IMDG)

14.1. UN number or ID number:

14.2. UN proper shipping name:

<u>14.3. Transport hazard class(es):</u>

14.4. Packing group:

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.



according to Regulation (EC) No 1907/2006

HANSA-FLEX OEL HVLPD 46

Page 8 of 8

Revision date: 03.07.2024 14.5. Environmental hazards ENVIRONMENTALLY HAZARDOUS: No 14.6. Special precautions for user Handling (Transport information): No special precautionary measures are necessary. See protective measures under point 7 and 8. 14.7. Maritime transport in bulk according to IMO instruments No information available. **SECTION 15: Regulatory information** 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulatory information Information according to Directive Not subject to 2012/18/EU (SEVESO III) 2012/18/EU (SEVESO III): Additional information Safety Data Sheet according to Regulation (EC) No 1907/2006 (amended by Regulation (EU) No 2020/878) National regulatory information Water hazard class (D): 1 - slightly hazardous to water Additional information Restricted to professional users. The receiver of our product is singularly responsible for adhering to existing laws and regulations. Observe in addition any national regulations! 15.2. Chemical safety assessment Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 8,9,13,14,15,16.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)